



Roundwood Removals 2025

Roundwood Removals 2025

You are completing this for the CSO (Central Statistics Office)

If the company details or structure have changed contact us on +353 (1) 498 4213 or email forestry@cso.ie

The purpose of the Roundwood Removals Survey is to compile statistics on removals of roundwood and roundwood biomass from privately-owned forests in Ireland. The survey results will contribute to meeting EU, industry, and national needs on forestry statistics.

The Roundwood Removals Survey is a statutory statistical survey conducted each year under the provisions of the Statistics (Roundwood Removals Survey) Order 2025 (S.I. No. 49 of 2025).

This questionnaire can be completed by:

The forest owner

- A forestry consultant or management company on behalf of the owner
- A harvesting contractor on behalf of the owner
- An enterprise that bought standing timber directly from the owner of a small forest should submit data on behalf of the owner e.g. a sawmill buying directly from a farmer
- To ensure that all removals are reported only once, please liaise with other persons that could submit information for the same removals.

[View the questions you will be asked in this survey](#)

Q1.1 Coniferous roundwood removals from privately-owned forests in Ireland by or on behalf of your company

Removals:

This term includes all harvesting including thinnings and storm damage.

Quantity:

The quantity of roundwood should be given in tonnes overbark. It should include all roundwood removals during {{survey year}} including thinnings. All weights should be reported at actual moisture content at the time of sale.

Please provide both tonnes and cubic metres if both are available.



Please use the following definitions for the roundwood removals questions:

Large sawlog: Roundwood with a top diameter of 20 cm or more and a typical length of between 3.7 and 7.3 metres. They are used for the manufacture of sawn timber largely for use by the construction industry.

Small sawlog (palletwood): Roundwood with a top diameter of 14-19 cm and a typical length of between 2.0 and 3.6 metres are classified as small sawlog (palletwood). It is suitable for use as packaging and for making garden furniture.

Stakewood: Roundwood with a top diameter of between 7-13 cm and a typical length of between 1.5 and 1.9 metres should be classified as stakewood if it is to be used for stakes and fencing.

Pulpwood: Pulpwood should have a top diameter of between 7-13 cm and with a length of around 3 metres. Pulpwood is used to produce pulp, door panels, particle board, oriented strand board (OSB), medium-density fibreboard (MDF), and other fibreboard. Pulpwood that has been converted to woodchip onsite should be entered in the Woodchip category.

Fuelwood: Wood removals sold for firewood. Please include removals under the Forestry for Fibre scheme if the roundwood was removed to be used as fuelwood.

Roundwood purchased for use as biomass: All roundwood removals for energy biomass use should be included in this category. If the roundwood was chipped at the forest then include it under Woodchip. Please include removals under the Forestry for Fibre scheme if the roundwood was removed to be used as biomass.

Woodchip: Pulpwood and other woody material that has been converted to woodchip at the forest should be included here. Please include removals under the Forestry for Fibre scheme if the roundwood was chipped onsite

Short rotation coppice: SRC is wood grown for energy purposes e.g. willow.

Other woody material: This category includes brash (lop and top) and tree stumps.



Large sawlog (Tonnes)

Roundwood with a top diameter of 20 cm or more and a typical length of between 3.7 and 7.3 metres.

Large sawlog (Cubic metres)

Roundwood with a top diameter of 20 cm or more and a typical length of between 3.7 and 7.3 metres.

Small sawlog (Tonnes)

Roundwood with a top diameter of 14-19 cm and a typical length of between 2.0 and 3.6 metres

Small sawlog (Cubic metres)

Roundwood with a top diameter of 14-19 cm and a typical length of between 2.0 and 3.6 metres.

Stakewood (Tonnes)

Roundwood used for stakes and fencing with a top diameter of 7-13 cm and a typical length of between 1.5 and 1.9 metres.

Stakewood (Cubic metres)

Roundwood used for stakes and fencing with a top diameter of 7-13 cm and a typical length of between 1.5 and 1.9 metres.

Pulpwood (Tonnes)

Pulpwood should have a top diameter of between 7-13 cm and with a length of around 3 metres.

Exclude: Pulpwood that has been converted to woodchip onsite.



Pulpwood (Cubic metres)

Pulpwood should have a top diameter of between 7-13 cm and with a length of around 3 metres.

Exclude: Pulpwood that has been converted to woodchip onsite.

Fuelwood (Tonnes)

Wood removals sold for firewood.

Include: Removals under the Forestry for Fibre scheme if the roundwood was removed to be fuelwood.

Fuelwood (Cubic metres)

Wood removals sold for firewood.

Include: Removals under the Forestry for Fibre scheme if the roundwood was removed to be fuelwood.

Roundwood purchased for use as biomass (Tonnes)

Include:

- All roundwood removals for energy biomass use
- Removals under the Forestry for Fibre scheme if the roundwood was removed to be biomass

Exclude: Roundwood converted at the forest to woodchip.

Roundwood purchased for use as biomass (Cubic metres)

Include:

- All roundwood removals for energy biomass use
- Removals under the Forestry for Fibre scheme if the roundwood was removed to be biomass

Exclude: Roundwood converted at the forest to woodchip.

Woodchip (Tonnes)

Include:

- Pulpwood and other woody material that has been converted to woodchip at the forest
- Removals under the Forestry for Fibre scheme if the roundwood was chipped onsite



Short rotation coppice (Tonnes)

Wood grown for energy purposes (e.g. willow).

Other woody material (Tonnes)

Includes: Brash (lop and top) and tree stumps.

Q1.2 Non-coniferous roundwood removals from privately-owned forests in Ireland by or on behalf of your company

Removals:

This term includes all harvesting including thinnings and storm damage.

Quantity:

The quantity of roundwood should be given in tonnes overbark. It should include all roundwood removals during {{survey year}} including thinnings. All weights should be reported at actual moisture content at the time of sale.

Please provide both tonnes and cubic metres if both are available.

Please use the following definitions for the roundwood removals questions:

Large sawlog: Roundwood with a top diameter of 20 cm or more and a typical length of between 3.7 and 7.3 metres. They are used for the manufacture of sawn timber largely for use by the construction industry.

Small sawlog (palletwood): Roundwood with a top diameter of 14-19 cm and a typical length of between 2.0 and 3.6 metres are classified as small sawlog (palletwood). It is suitable for use as packaging and for making garden furniture.

Stakewood: Roundwood with a top diameter of between 7-13 cm and a typical length of between 1.5 and 1.9 metres should be classified as stakewood if it is to be used for stakes and fencing.

Pulpwood: Pulpwood should have a top diameter of between 7-13 cm and with a length of around 3 metres. Pulpwood is used to produce pulp, door panels, particle board, oriented strand board (OSB), medium-density fibreboard (MDF), and other fibreboard. Pulpwood that has been converted to woodchip onsite should be entered in the Woodchip category.

Fuelwood: Wood removals sold for firewood. Please include removals under the Forestry for Fibre scheme if the roundwood was removed to be used as fuelwood.

Roundwood purchased for use as biomass: All roundwood removals for energy biomass use should be included in this category. If the roundwood was chipped at the forest then include it



under Woodchip. Please include removals under the Forestry for Fibre scheme if the roundwood was removed to be used as biomass.

Woodchip: Pulpwood and other woody material that has been converted to woodchip at the forest should be included here. Please include removals under the Forestry for Fibre scheme if the roundwood was chipped onsite

Short rotation coppice: SRC is wood grown for energy purposes e.g. willow.

Other woody material: This category includes brash (lop and top) and tree stumps.

Large sawlog (Tonnes)

Roundwood with a top diameter of 20 cm or more and a typical length of between 3.7 and 7.3 metres.

Large sawlog (Cubic metres)

Roundwood with a top diameter of 20 cm or more and a typical length of between 3.7 and 7.3 metres.

Small sawlog (Tonnes)

Roundwood with a top diameter of 14-19 cm and a typical length of between 2.0 and 3.6 metres

Small sawlog (Cubic metres)

Roundwood with a top diameter of 14-19 cm and a typical length of between 2.0 and 3.6 metres.

Stakewood (Tonnes)

Roundwood used for stakes and fencing with a top diameter of 7-13 cm and a typical length of between 1.5 and 1.9 metres.



Stakewood (Cubic metres)

Roundwood used for stakes and fencing with a top diameter of 7-13 cm and a typical length of between 1.5 and 1.9 metres.

Pulpwood (Tonnes)

Pulpwood should have a top diameter of between 7-13 cm and with a length of around 3 metres.

Exclude: Pulpwood that has been converted to woodchip onsite.

Pulpwood (Cubic metres)

Pulpwood should have a top diameter of between 7-13 cm and with a length of around 3 metres.

Exclude: Pulpwood that has been converted to woodchip onsite.

Fuelwood (Tonnes)

Wood removals sold for firewood.

Include: Removals under the Forestry for Fibre scheme if the roundwood was removed to be fuelwood.

Fuelwood (Cubic metres)

Wood removals sold for firewood.

Include: Removals under the Forestry for Fibre scheme if the roundwood was removed to be fuelwood.

Roundwood purchased for use as biomass (Tonnes)

Include:

- All roundwood removals for energy biomass use
- Removals under the Forestry for Fibre scheme if the roundwood was removed to be biomass

Exclude: Roundwood converted at the forest to woodchip.



Roundwood purchased for use as biomass (Cubic metres)

Include:

- All roundwood removals for energy biomass use
- Removals under the Forestry for Fibre scheme if the roundwood was removed to be biomass

Exclude: Roundwood converted at the forest to woodchip.

Woodchip (Tonnes)

Include:

Pulpwood and other woody material that has been converted to woodchip at the forest
Removals under the Forestry for Fibre scheme if the roundwood was chipped onsite

Short rotation coppice (Tonnes)

Wood grown for energy purposes (e.g. willow).

Other woody material (Tonnes)

Includes: Brush (lop and top) and tree stumps.

Q2. Standing timber value of roundwood removals from privately-owned forests in Ireland by or on behalf of your company

The standing timber or stumpage value is the gross amount received by the forest owner excluding VAT.

This value should not be adjusted to account for harvesting, extraction, transportation, and other costs.

Please report the data in thousand euro, for example insert 25 for €25,000.

Total value of roundwood removals



Q2.1 Coniferous roundwood removals standing timber value from privately-owned forests in Ireland by or on behalf of your company

The standing timber or stumpage value is the gross amount received by the forest owner excluding VAT.

This value should not be adjusted to account for harvesting, extraction, transportation, and other costs.

Please report the data in thousand euro, for example insert 25 for €25,000. account for harvesting, extraction, transportation, and other costs.

Please report the data in thousand euro, for example insert 25 for €25,000.

Please use the following definitions for the roundwood removals questions:

Large sawlog: Roundwood with a top diameter of 20 cm or more and a typical length of between 3.7 and 7.3 metres. They are used for the manufacture of sawn timber largely for use by the construction industry.

Small sawlog (palletwood): Roundwood with a top diameter of 14-19 cm and a typical length of between 2.0 and 3.6 metres are classified as small sawlog (palletwood). It is suitable for use as packaging and for making garden furniture.

Stakewood: Roundwood with a top diameter of between 7-13 cm and a typical length of between 1.5 and 1.9 metres should be classified as stakewood if it is to be used for stakes and fencing.

Pulpwood: Pulpwood should have a top diameter of between 7-13 cm and with a length of around 3 metres. Pulpwood is used to produce pulp, door panels, particle board, oriented strand board (OSB), medium-density fibreboard (MDF), and other fibreboard. Pulpwood that has been converted to woodchip onsite should be entered in the Woodchip category.

Fuelwood: Wood removals sold for firewood. Please include removals under the Forestry for Fibre scheme if the roundwood was removed to be used as fuelwood.

Roundwood purchased for use as biomass: All roundwood removals for energy biomass use should be included in this category. If the roundwood was chipped at the forest then include it under Woodchip. Please include removals under the Forestry for Fibre scheme if the roundwood was removed to be used as biomass.

Woodchip: Pulpwood and other woody material that has been converted to woodchip at the forest should be included here. Please include removals under the Forestry for Fibre scheme if the roundwood was chipped onsite

Short rotation coppice: SRC is wood grown for energy purposes e.g. willow.

Other woody material: This category includes brash (lop and top) and tree stumps.



Total coniferous roundwood removals

Large sawlog

Coniferous roundwood with a top diameter of 20 cm or more and a typical length of between 3.7 and 7.3 metres.

Small sawlog

Coniferous roundwood with a top diameter of 14-19 cm and a typical length of between 2.0 and 3.6 metres.

Stakewood

Coniferous roundwood used for stakes and fencing with a top diameter of 7-13 cm and a typical length of between 1.5 and 1.9 metres.

Pulpwood

Coniferous pulpwood should have a top diameter of between 7-13 cm and with a length of around 3 metres.

Exclude: Pulpwood that has been converted to woodchip onsite.

Fuelwood

Coniferous wood removals sold for firewood.

Include: Removals under the Forestry for Fibre scheme if the roundwood was removed to be fuelwood.



Roundwood biomass removals

Include:

- All coniferous roundwood removals for energy biomass use
- Removals under the Forestry for Fibre scheme if the roundwood was removed to be biomass

Exclude: Roundwood converted at the forest to woodchip.

Q2.2 Non-coniferous roundwood removals from privately-owned forests in Ireland by or on behalf of your company

The standing timber or stumpage value is the gross amount received by the forest owner excluding VAT.

This value should not be adjusted to account for harvesting, extraction, transportation, and other costs.

Please report the data in thousand euro, for example insert 25 for €25,000.

Total non-coniferous roundwood removals

Non-coniferous roundwood biomass removals

Include:

- All non-coniferous roundwood removals for energy biomass use
- Removals under the Forestry for Fibre scheme if the roundwood was removed to be biomass

Exclude: Roundwood converted at the forest to woodchip.



Comments, Administration Burden and Contact Details

Please add any comments that would help us to interpret the data provided and avoid further queries:

How many minutes did it take you to collect the data for this form?

Declaration Please note: Queries or future surveys from the CSO may be directed to the email or phone number provided by you.

Name:

Position:

Phone:

Email:

Website of Enterprise:

Eircode of Enterprise: